

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION  
INDEXES OF FILE NO. C.

DEC 28 9 49 PM '66

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name <b>Sample</b>
9. Well No. <b>1</b>
10. Field and Pool, or Wildcat <b>Wildcat</b>
12. County <b>Roosevelt</b>

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator <b>Morris R. Antweil</b>	
3. Address of Operator <b>P. O. Box 2010, Hobbs, New Mexico</b>	
4. Location of Well UNIT LETTER <b>G</b> <b>1980</b> FEET FROM THE <b>North</b> LINE AND <b>1980</b> FEET FROM <b>East</b> <b>27</b> TOWNSHIP <b>7S</b> RANGE <b>34E</b> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) <b>KB 4281</b>	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well 12:00 Midnight 12-20-66. Ran and set 410' of 8-5/8", 32#/ft. surface casing, cemented with 300 sxs. regular cement and 2% calcium chloride. Cement circulated. W.O.C. 24 hrs. Tested casing with 800 psi. for 30 minutes. No pressure decline.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Paula Velasco* TITLE Agent DATE 12-22-66  
APPROVED BY *John A. Stoney* TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: