

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	1742	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt		T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt		T. Aloka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	2320	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers		T. Devonian	T. Menefee	T. Madison
T. Queen		T. Silurian	T. Point Lookout	T. Ribert
T. Grayburg	3559	T. Montoya	T. Mancos	T. McCracken
T. San Andres		T. Simpson	T. Gallup	T. Ignacio Quito
T. Glorieta		T. McKee	T. Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	T. T.
T. Blinberry		T. Gr. Wash	T. Morrison	T. T.
T. Tubb		T. Granite	T. Todillo	T. T.
T. Drinkard		T. Delaware Sand	T. Entrada	T. T.
T. Abo		T. Bone Springs	T. Wingate	T. T.
T. Wolfcamp		T. T.	T. Chinle	T. T.
T. Penn.		T. T.	T. Permian	T. T.
T. Cisco (Bough C)		T. T.	T. Penn. "A"	T. T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness In Feet	Formation	From	To	Thickness In Feet	Formation
0	200	200	Surface sand & caliche				
200	1742	1542	Red Beds				
1742	2320	578	Anhydrite and salt				
2320	3559	1239	Sand, Anhydrite, Shale				
3559		781	Dolomite				

HOBBS OFFICE G. C. C.
FEB 7 11 44 AM '67

INCLINATION REPORT

TOM L. INGRAM
100 South Kentucky
Roswell, New Mexico

STATE "D" WELL NO. 1
660' FSL & 1980' FWL Sec 31, T-7-S, R-31-E,
Roosevelt County, New Mexico

RECORD OF INCLINATION

<u>Depth (feet)</u>	<u>Angle of Inclination (degrees)</u>	<u>Displacement (feet)</u>	<u>Accumulative Displacement (feet)</u>
318	3/4	4.17	4.17
810	3/4	6.44	10.61
1,300	3/4	6.42	17.03
1,800	1	8.75	25.78
2,327	1	9.22	35.00
2,911	1 1/4	12.73	47.73
3,490	1 3/4	17.66	65.39
3,791	1	5.27	70.66
4,038	1	4.32	74.98
4,340	3/4	3.96	78.94

I hereby certify that I have personal knowledge of the data and facts placed on this report, and that such information is true and complete.


Verna Drilling Company

Sworn and Subscribed before me, this the 31st day of January, 1967.


Notary Public in and for
Hockley County, Texas