

|                            |  |               |  |              |  |
|----------------------------|--|---------------|--|--------------|--|
| COUNTY ROOSEVELT           |  | FIELD Wildcat |  | STATE NM     |  |
| OPR HUBER, J. M. CORP.     |  |               |  | MAP          |  |
| 1 Reid "12"                |  |               |  |              |  |
| Sec. 12, T-8-S, R-35-E     |  |               |  | CO-ORD       |  |
| 660' FSL, 660' FEL of Sec. |  |               |  | 30-041-20031 |  |
| Spd 7-12-67                |  |               |  |              |  |
| CLASS                      |  |               |  |              |  |
| Cmp 8-8-67                 |  | FORMATION     |  | DATUM        |  |
| CSG & SX - TUBING          |  | FORMATION     |  | DATUM        |  |
| 8 5/8" 446' 275            |  |               |  |              |  |
| 4 1/2" 5025' 150           |  |               |  |              |  |
|                            |  |               |  |              |  |
|                            |  |               |  |              |  |
| LOGS EL GR RA IND HC A     |  |               |  |              |  |
|                            |  | TD 5025'      |  |              |  |
| PLUGGED & ABANDONED        |  |               |  |              |  |

Distribution limited and publication prohibited by subscribers' agreement.  
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

|       |                  |         |
|-------|------------------|---------|
| CONT. | PROP DEPTH 5100' | TYPE RT |
| DATE  |                  |         |

F.R. 6-29-67; Opr's Elev. 4153' KB  
 PD 5100' - SA  
 7-17-67 Drlg. 4040'.  
 7-24-67 TD 4950', on DST 4892-4950'.  
 7-31-67 TD 5025', WOC.  
 DST 4892-4950', open 1 hr 5 mins,  
 rec 60' Sli O&GCM + 654' Sli OC Salt Wtr,  
 1 hr 15 min ISIP 1675#, FP 140-399#,  
 1 hr 30 min FSIP 1613#, HP 3000-2980#.  
 Cored 4950-5025', rec 73' being:  
 35' dense dolo;  
 10' dense dolo., w/scatt stain;  
 23' dolo., w/stain; & 7' porosity;  
 5' shly dolo.

7-31-67 Cont.

DST 4970-5025', open 1 hr 30 mins  
Rec 30' Very Sli GCM  
1 hr 30 min ISIP 1873#, FP 52-68#,  
2 hr 30 min FSIP 1635#.  
SP DST 4828-80', open 30 mins,  
rec 360' DM, w/NS,  
1 hr 25 min ISIP 1724#, FP 28-212#,  
1 hr 30 min FSIP 1839#.

8-7-67

TD 5025', prep P&A.  
Perf 4996-5010' W/2 SPF  
Acid (4996-5010') 250 gals.  
Swbd 46 BLW in 6 hrs & swbd dry (4996-5010')  
Acid (4996-5010') 3000 gals 15%  
Swbd 71 BLW in 12 hrs & swbd dry (4996-5010')

8-14-67

Acid (4996-5010') 3000 gals.  
Swbd load in 20 hrs.  
Swbd 3 BF w/tr. oil in 5 hrs (4996-5010')  
TD 5025', PLUGGED & ABANDONED  
LOG TOPS: Anhydrite 2345', Yates 2760',  
San Andres 4016', Pi Zone 4624', Porosity I  
4778', Porosity II 4834', Porosity III  
4898', Porosity IV 4976'.