

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
<b>K-3995</b>

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>Taylor Pruitt</b>	8. Farm or Lease Name <b>Anderson State</b>
3. Address of Operator <b>c/o Oil Reports &amp; Gas Services, Box 763, Hobbs, New Mexico</b>	9. Well No. <b>5</b>
4. Location of Well UNIT LETTER <b>H</b> <b>1980</b> FEET FROM THE <b>North</b> LINE AND <b>660</b> FEET FROM THE <b>East</b> LINE, SECTION <b>36</b> TOWNSHIP <b>7 S</b> RANGE <b>32 E</b> NMPM.	10. Field and Pool, or Wildcat <b>Chaveroo San Andrae</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>4473.5 GR</b>	12. County <b>Roosevelt</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12 1/4" hole 7:45 PM 2/23/68. Cemented 8 5/8" 20# casing at 344 feet with 225 sacks class "H" cement 2% calcium chloride. Cement circulated. Plug down 2:00 AM 2/24/68. WOC 18 hours and tested casing with 1100# for 30 minutes, test O.K.

Cemented 5 1/2" 14# & 15.5# casing at 4471 with 300 sacks Halliburton light cement & 300 sacks Incor Pozmix, 2% gel, 0.75% CFR-2, 11# salt per sack. Plug down 2:00 PM 3/2/68. WOC 48 hours and tested casing with 1800# for 30 minutes, test O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *A. L. Smith* TITLE Agent DATE 3/6/68

APPROVED BY *Joel H. Hines* TITLE  DATE

CONDITIONS OF APPROVAL, IF ANY: