c. 1973	UNITED STATES								
	;			THE INTER	RIOR				
SUND	RY	NOTICE	S AND	REPORTS	ON	WELLS			

Re-entry

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

Suite 510, 1776 Lincoln St., Denver, CO 80203 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,

other

AT SURFACE: 1980' FSL, 660' FWL, Unit L

Same

gas

SUNDANCE OIL COMPANY 3. ADDRESS OF OPERATOR

AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

2. NAME OF OPERATOR

well

5. LEASE	8 6 5 ½	5	ਹ ਼ ਹੈ							
NM-15019	要品質		ឆ្នំ≶្							
6. IF INDIAN, ALLOTTEE OR TRIBE NAME										
·	5555	Ç	, ei	-						
7. UNIT AGREEMENT NAME										
	_부 등측 분	=								
8. FARM OR I	EASE NAM	Ε	5 <u>2</u> ⊆							
Cone Federa	al Ree	Ţ.	0 0 F.Y.							
9. WELL NO.	ä., 5	3.	± ± €.							
13	명류구중	<u>.</u>	र्वे हे ह							
10. FIELD OR		 -	125							
Tomahawk, S	San Andr	^es	# <u>#</u> []							
11. SEC., T., R	., M., OR B	LK. AN	D SURVE	Y OR						
AREA		1,4	12 最级是 1							
NW SW Sect	<u>ion 31,</u>	T.7S	., R.3	2E.						
12. COUNTY OR PARISH 13. STATE										
Roosevelt	2 x 2 x 1 x 1 x 1 x 1 x 1 x 1 x 1 x 1 x	New	Mexico							
14. API NO.	EFEL	7	इ.ज.१२							
	<u> </u>	-,	4 3 5 5							
15. ELEVATION	VS (SHOW	DF, K	DB, AND	WD)						
4467' GL	A 647	(**)	1500	6						
	I. F. J. S.	:	11.17.12	///						
		ر آل	"上角"	9						
		يا <i>ڪول</i> آ		0						
(NOTE: Report	الاستان الاستا المستان الاستان الاستا	⊃ ુ. ultiple.co	10	7						

change on Form 9

(other) SET PRODUCTION 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SUBSEQUENT REPORT OF:

Reamed old hole Re-entered 6/29/79. Washed and cleaned old hole to 4025. (6 3/4") from 4025' to 4300'. Reamed to 7 7/8" hole. Total depth 4300'. Ran 104 jts. (4321') $4\frac{1}{2}$ ", 10.5#, K-55, R-3 casing to 4300'. Cemented with 460 sx Class H, 3% Econolite, 4# flocele and 300 sx 50/50 Pozmix, 2% gel, 8# salt, 4# flocele. Circulated 10 sx to surface. Plug down at 8 a.m. 7/2/79. up to 1800#, okay. WOCU.

Subsurface Safety/Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct <u>Production</u> _ DATE _ (This space for Federal or State office use)

APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:

DATE

See Instructions on Reverse Side

