STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

me, ar Corich heccives		
POLTUBIATION		
SANTA FE		
FILE		
U.S.G.S.	1	
LIND OFFICE		
OPERATOR	1	

OIL CONSERVATION DIVISION P. O. BOX 2088 SANTA FE, NEW MEXICO:87501

Form C-103 Revised 10-1:

Sc. Indicate Type of Lease
State X F
5, State Off 6 Gas Lease No.

OG-174

DATE January 3, 1985

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL ON TO DEEP HI OR PLUG DACK TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR PROMIT - FORM C-101) FOR SUCK PROPOSALS.)		
I. OIL CAS OTHER-	7. Unit Agreement Name Todd Lower San Andres Uni	
2. Nume of Operator	8. Form or Lease Name	
MURPHY OPERATING CORPORATION	TLSA Unit Sec. 31	
3. Address of Operator .	9. Well No.	
P. O. Drawer 2648, Roswell, New Mexico 88201	10	
4. Location of Well	10. Field and Pool, or Wildcat	
UNIT LETTER J 2180 FEET FROM THE SOUTH LINE AND FEET FROM	Todd Lower San Andres Asso	
THE East LINE, SECTION 31 TOWNSHIP 7 SOUTH RANGE 36 East NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.) 4136 GR	12. County Roosevelt	
Check Appropriate Box To Indicate Nature of Notice, Report or Otl NOTICE OF INTENTION TO: SUBSEQUENT	er Data REPORT OF:	
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CABING OTHER OTHER	ALTERING CASING PLUG AND ABANDONMENT dizing X	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	estimated date of starting any propose	
11-15-84 RU PU & unseat pump. TOH w/rods & pump. TIH w/tag jt. & tagge TOH w/2-3/8" tbg. & SLM.	ed btm. @ 4310' G.L.	
RU & TIH & ran Gamma Ray Neutron Log. Logged to 3950' (TD 4320 (log attached). TIH w/perf. gun & perforated 41' @ 1 JSPF from w/perf. gun. TIH w/UNI VI Pkr. & set pkr. @ 4204'. TOH & acid Xylene, 2000 gals 28% NEFE & 500# salt block & overflushed w/10 & pressured while treating well @ avg. press. 1000 psi, max. prate of 5.8 BPM & @ max. rate of 6.4 BPM. ISIP 500 psi. in 2 max. TIH & released pkr. & TOH w/same. TIH w/137 jts. 2-3/8" tbg., nipple @ 4298.75'. TOH. RU WH, set slips & changed tbg. elev 5/8" rods, 68 - 3/4" rods, 2' - 5/8" sub, 6' - 3/4" sub & 16' liner & TOH. Well pumping from 4302.85'. RD.	n 4280' - 4320'. TOH dized w/500 gals. 000 gals. 2% KCl water ress. 2600 psi & @ avg. min. well on vacuum. 3' perf. sub. & seat . TIH w/pump & 112 -	

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CRIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR