	Form C=103
	Form C-103 Supersedes Old
	C-102 and C-103
NO. OF COPIES RECEIVED	Effective 1-1-65
DISTRIBUTION NEW MEXICO OIL CONSERVATION COMMISSION	m of Legse
DISTRIBUTION NEW MEXICO	5a, Indicate Type of Lease
SANTA FE	State A
FILE	5. State Oil & Gas Lease No.
U.S.G.S.	0G-174
LAND OFFICE	VIIIIIIIIII
OPERATOR SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. (DO NOT USE THIS FORM FOR PROPOSALS.) (DO NOT USE THIS FORM FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)	
TO A DIFFERENT RESERVOIR.	7. Unit Agreement Name
SUNDRY NO ICLE OR TO DEEPEN OR SUCH PROPOSALS.)	7. Only Agreem
(DO NOT USE THIS FORM FOR PERMIT - USE MAPPLICATION FOR PERMIT -	8. Farm or Lease Name
	8. Farm or Lease Name Atlantic-Smith State
OIL W GAS OTHER.	
WELL C	9. Well No.
Name of Operator FRANKLIN, ASTON & FAIR, INC.	2
FRANKLIN, ASTON	1 (Unde stignated) ildeat
3. Address of Operator P. O. Box 1090, Roswell, New Mexico 88201 P. O. Box 1090, Roswell, New Mexico 88201	Todd Lower San Andres
P. O. Box 1090, ROSWETT, 100	ROM TOTAL TOTAL
4. Location of Well 2180 FFET FROM THE South LINE AND	
4100	
UNIT LETTER 75	MBW: (1)
TOWNSHIP	12. County
1 sabor DF, RI, OR,	Rooseveit
15. Elevation (Show whether 135' KB 4126.1' GR , 4135' KB	
Check Appropriate Box To Indicate Nature of Notice, Report of Subsequents	r Other Data
SUBSEQUENCE Nature of Notice,	JENT REPORT OF:
Check Appropriate Dox 25	Γ
NOTICE OF INTENTION	ALTERING CAST
REMEDIAL WORK	PLUG AND ABANDONMENT
PLUG AND ABANDON L	
PERFORM REMEDIAL WORK COMMERCE	<u> </u>
CHANGE PLANS	
OTHER	
PULL ON ACTION	any propo
aine pertinent dates, it	icluding estimated date of
OTHER (Clearly state all pertinent details, and give posture	
1.0	
Proposite Proposed or Completed Operations	
OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, in work) SEE RULE 1103.	R using 250 sacks cement.
17. Describe Proposed or Completed Operations (work) SEE RULE 1903.	B using 250 sacks cement.
17. Describe Proposed or Completed Operations (work) SEE RULE 1103. 27. 1068 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
17. Describe Proposed or Completed Operations, work) SEE RULE 1103. On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K	B using 250 sacks cement. nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	Busing 256 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	Busing 256 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	Busing 256 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	Busing 256 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	B using 250 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	Busing 256 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	B using 250 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	B using 256 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	B using 256 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	B using 256 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton.	B using 256 nutes, pressure held.
On January 27, 1968 set 4326' of 5 1/2", 14# casing at 4336' K On January 31 pressured up on casing to 600 psi and held 30 mi Cementing work done by Halliburton. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief	B using 256 nutes, pressure held.