

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>K-4866</b>

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>Sunray DX Oil Company</b>	8. Farm or Lease Name <b>New Mexico "HH" State</b>
3. Address of Operator <b>P. O. Box 1416 - Roswell, New Mexico</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>L</b> <b>1980</b> FEET FROM THE <b>South</b> LINE AND <b>660</b> FEET FROM THE <b>West</b> LINE, SECTION <b>20</b> TOWNSHIP <b>7-S</b> RANGE <b>36-E</b> NMPM.	10. Field and Pool, or Wildcat <b>Undesignated</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>4159 D.F.</b>	12. County <b>Roosevelt</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Drilled 11" hole to 371'. Ran 8-5/8", 24#, J-55 csg to 364'. Cmt w/250 sxs reg. w/2% CaCl<sub>2</sub>. Circ 20 sxs to surface. WOC 18 hrs. Tested csg to 1000# for 30 min. OK.
2. Drilled 7-7/8" hole to TD 4370'. Ran Open Hole Logs; GR-Density, Laterolog, and Microlaterolog.
3. Ran 4-1/2", 9.5#, J-55 csg to 4369. Cmt. w/200 sxs Incore Pos w/8# salt/sx. WOC 24 hrs. Tested csg to 1500# for 30 min. OK. Top of cement by temp. survey 3650'.
4. Ran PFC Log and perf four (4) holes. 1 each @ 4284, 4286, 4288, 4291.
5. Acidized w/1000 gal DS-30 acid. Recover load.
6. Frac w/30000 gal crude w/1/40# Adomite per gal and 30,000# sand.
7. Now recovering load.
8. Will test and place well on production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ralph L. Maness TITLE Acting District Engineer DATE February 1, 1968

APPROVED BY John W. Runyan TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: