

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL:		OIL WELL ☐	GAS WELL ☐	DRY ☒	Other _____		
b. TYPE OF COMPLETION:		NEW WELL ☐	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. RESVR. ☐	Other _____
2. NAME OF OPERATOR FRANKLIN, ASTON & FAIR, INC.						5. LEASE DESIGNATION AND SERIAL NO. NM 0139989	
3. ADDRESS OF OPERATOR P. O. Box 1090, Roswell, New Mexico 88201						6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 660' FNSL's Section 30-7S-36E At top prod. interval reported below At total depth						7. UNIT AGREEMENT NAME	
14. PERMIT NO.						8. FARM OR LEASE NAME Llivaudais Federal	
DATE ISSUED						9. WELL NO. 6	
15. DATE SPUDDED 6-16-68						10. FIELD AND POOL, OR WILDCAT Todd Lower San Andres	
16. DATE T.D. REACHED 6-26-68						11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 30-7S-36E, N.M.P.M.	
17. DATE COMPL. (Ready to prod.) Dry						12. COUNTY OR PARISH Roosevelt	
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 4145.9' GL, 4154.4' KB						13. STATE New Mexico	
20. TOTAL DEPTH, MD & TVD 4306'		21. PLUG, BACK T.D., MD & TVD		22. IF MULTIPLE COMPL., HOW MANY*		19. ELEV. CASINGHEAD	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*						23. INTERVALS DRILLED BY ROTARY TOOLS 0 - T.D.	
25. WAS DIRECTIONAL SURVEY MADE						CABLE TOOLS	
26. TYPE ELECTRIC AND OTHER LOGS RUN Gamma Ray-Sonic						27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)							
CASING SIZE		WEIGHT, LB./FT.		DEPTH SET (MD)		HOLE SIZE	
8 5/8"		24#		293' KB		12 1/4"	
5 1/2"		14#		4306' KB		7 7/8"	
29. LINER RECORD				30. TUBING RECORD			
SIZE		TOP (MD)		BOTTOM (MD)		PACKER SET (MD)	
31. PERFORATION RECORD (Interval, size and number)				32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.			
One shot per foot at the following depths: 4232', 4235', 4248', 4250', 4253', 4263', 4266', 4268', 4272', 4277', 4285'				DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED	
				4232'-4285'		3,000 gallons 15% DS-30 acid	
				4232'-4285'		Sand/oil fraced with 30,000 gallon lease oil and 30,000# 20/40 sand with 900# Adomite Mark II additive.	
33. PRODUCTION							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
Dry						Dry & ASD	
DATE OF TEST		HOURS TESTED		CHOKE SIZE		PROD'N. FOR TEST PERIOD	
FLOW. TUBING PRESS.		CASING PRESSURE		CALCULATED 24-HOUR RATE		OIL—BBL.	
						GAS—MCF.	
						WATER—BBL.	
						OIL GRAVITY-API (CORR.)	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)						TEST WITNESSED BY	
35. LIST OF ATTACHMENTS							
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records							
SIGNED Grant M Smith		TITLE Geologist		DATE 12-18-68			

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:		38.	
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES		GEOLOGIC MARKERS	
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
San Andres (Slaughter A) (Slaughter B) T.D.	3470' 4116' 4226' 4306'		

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH