

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O.G.C.
NEW MEXICO OIL CONSERVATION COMMISSION

May 17 10 09 AM '68

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Humble Tucker
9. Well No. 3
10. Field and Pool, or Wildcat Chaveroo San Andres
12. County Reesevelt

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Taylor Pruitt
3. Address of Operator c/o Oil Reports & Gas Services, Box 763, Hobbs, New Mexico
4. Location of Well UNIT LETTER L , 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 25 TOWNSHIP 7 S RANGE 32 E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4446.2

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12 1/4" hole 5/2/68. Cemented 8 5/8" 20# casing at 345 feet with 225 sacks class "H" 2% calcium chloride. Cement circulated. Bumped plug with 350# 6:00 PM 5/2/68. WOC 18 hours and tested casing with 1800# for 30 minutes, test O.K.

Cemented 5 1/2" 14# & 15.5# J-55 casing at 4498 with 300 sacks Halliburton lite cement and 350 sacks Incer Pozmix, 6% gal, 11# salt per sack, 0.75% CFR-2. Bumped plug with 1500# 11:50 AM 5/10/68. WOC 96 hours and tested casing with 2000# for 30 minutes, test O.K.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

IGNED A. L. Smith TITLE Agent DATE 5/16/68
APPROVED BY John W. Runyan TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: