

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
CORRECTED REPORTSUBMIT IN TRIPLICATE*
(Other instruction reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 0367781-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shell Federal 35

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 35, T-7-S, R=32-E

12. COUNTY OR PARISH

Roosevelt New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Southwestern Natural Gas, Inc.

3. ADDRESS OF OPERATOR

900 Bank of the Southwest, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980' FNL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4483 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Corrected Report

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Original TD 9097 (Bough "C")

7-15-68: Cut 4-1/2" casing @ 7900' and pulled out. Set 15 sk plug @ 8700'
Set 50 sk plug @ 7900' and 75 sk plug @ 5,000'.

7-16-68: Logging.

7-17-68: Perforated San ANDres zone at 4194, 4201, 06, 24, 55, 58, 62,
83, 89, 4302, 19, 63, 67, 71. Job complete 5:00 p.m., 7-17.7-18-68: Acidized perfs from 4363 to 4371 w/500 gals acid. Acidized
perfs from 4255 to 4319 w/1000 gals and 14 ball sealers.

Acidized perfs from 4194 to 4224 w/500 gals and 12 ball sealers.

7-21-68: Fraced w/40,000 gals refined oil plus 2# sand/gallon.


7-22-68: Ran rods and tubing.

7-23-68: Put on pump

7-24-68: Pumping back load.

18. I hereby certify that the foregoing is true and correct

SIGNED



TITLE

Office Manager

DATE

7-29-68

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

SEP 5 1968

*See Instructions on Reverse Side

GORDON
ACTING DISTRICT ENGINEER