

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<p><b>SUNDRY NOTICES AND REPORTS ON WELLS</b> DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.</p>		<p>5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p>
<p>1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <u>Drill</u></p>		<p>5. State Oil &amp; Gas Lease No.</p>
<p>2. Name of Operator <u>Cayman Corporation</u></p>		<p>7. Unit Agreement Name</p>
<p>3. Address of Operator <u>P. O. Box 2099, Palos Verdes Peninsula, Calif. 90274</u></p>		<p>8. Farm or Lease Name <u>Bow-Maxwell</u></p>
<p>4. Location of Well UNIT LETTER <u>G</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1979</u> FEET FROM THE <u>East</u> LINE, SECTION <u>9</u> TOWNSHIP <u>8-S</u> RANGE <u>36-E</u> NMPM.</p>		<p>9. Well No. <u>1</u></p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) <u>4112.8GR</u></p>		<p>10. Field and Pool, or Wildcat <u>Wildcat</u></p>
<p>12. County <u>Roosevelt</u></p>		

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-17-68 Placed 30 sack cement plug 12,945-13,065' and then 25 sack cement plugs at:

12,420 - 12,520  
9,585 - 9,685  
8,675 - 8,775

7,675 - 7,775  
5,375 - 5,475  
4,125 - 4,225

1- 6-69 Shot into and recovered 1515' of 8 5/8", 24# casing.  
Placed cement plugs at:  
1483 - 1533' 25 sx  
350 - 390' 25 sx  
surface 10 sx  
Installed marker  
9.3 lb/gal mud between all cement plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. Goodrich

TITLE Engineer

DATE 1-17-69

APPROVED BY John W. Runyan

TITLE Engineer

DATE 1-17-69

CONDITION OF APPROVAL, IF ANY: