

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65.

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Taylor Pruitt	8. Farm or Lease Name Tucker Hall
3. Address of Operator c/o Oil Reports & Gas Services, Box 763, Hobbs, New Mexico	9. Well No. 1
4. Location of Well UNIT LETTER 0 FEET FROM THE South LINE AND 1980 FEET FROM East 25 TOWNSHIP 7 S RANGE 32 E NMPM. THE LINE, SECTION TOWNSHIP RANGE NMPM.	10. Field and Pool, or Wildcat Chaverco-San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 4444.7 GR	12. County Roosevelt

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12 1/4" hole 11/14/68. Cemented 8 5/8" 20# casing at 338 feet with 225 sacks Type "H" cement, 2% calcium chloride. Cement Circulated. Bumped plug with 300# at 6:00 PM 11/14/68. WOC 18 hours and tested casing with 1,000# for 30 minutes, test O.K.

Cemented 5 1/2" 14# J-55 casing at 4498 with 200 sacks Class C Pozmix, 2% gel and 350 sacks Class C Pozmix, 2% gel, 12# salt per sack, 0.75% CFR-2. Bumped plug with 2000# at 3:30 PM 11/22/68. WOC 48 hours and tested casing with 2000# for 30 minutes, test O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. L. Smith TITLE Agent DATE 12/2/68
APPROVED BY John W. Runyan TITLE _____ DATE _____
CONDITION OF APPROVAL, IF ANY: