

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

5. LEASE DESIGNATION AND SERIAL NO.

NM 044216

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bluitt-Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

East Bluitt-San Andres

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec. 13-8S-37E, N.M.P.M.

12. COUNTY OR
PARISH

Roosevelt

13. STATE

New Mexico

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other _____b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____

2. NAME OF OPERATOR

FRANKLIN, ASTON & FAIR, INC.

3. ADDRESS OF OPERATOR

P. O. Box 1090, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1980' FSL & 1980' FEL Sec. 13-8S-37E

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

12-10-68

16. DATE T.D. REACHED

12-17-68

17. DATE COMPL. (Ready to prod.)

12-22-68

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3997.5' GR, 4009.5' KB

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

4694'

21. PLUG, BACK T.D., MD & TVD

22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0-T.D.

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

4645' - 4669' San Andres (Slaughter B)

25. WAS DIRECTIONAL
SURVEY MADE

Totco only

26. TYPE ELECTRIC AND OTHER LOGS RUN

Gamma Ray Sonic

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	20#	286'	12 1/4"	175 sx w/2% CaCl	
5 1/2"	14#	4694'	7 7/8"	275 sx w/2% Gel	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2"	4550'	4550'

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

4645, 4648, 4649, 4651, 4657, 4658,
4664, 4667, and 4669

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4645 - 4669	3,000 gal. reg. acid
4645 - 4669	6,000 gal. reg. acid

33.*

PRODUCTION

DATE FIRST PRODUCTION

12-22-68

PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)

Flowing

WELL STATUS (Producing or
shut-in)

Producing

DATE OF TEST

12-23-68

HOURS TESTED

24

CHOKE SIZE

32/64

PROD'N. FOR
TEST PERIOD

OIL—BBL.

165

GAS—MCF.

128

WATER—BBL.

0

GAS-OIL RATIO

776:1

FLOW. TUBING PRESS.

205#

CASING PRESSURE

CALCULATED
24-HOUR RATE

OIL—BBL.

GAS—MCF.

WATER—BBL.

OIL GRAVITY-API (CORR.)

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented

TEST WITNESSED BY

J. W. Brasfield

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE Geologist

DATE 12-26-68

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool. **Item 33:** Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES			38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
San Andres	3848'				
Slaughter (A)	4564'	4620'			
1st Anhydrite	4620'	4634'			
Slaughter (B)	4634'	4680'			
2nd Anhydrite	4680'	4694' TD			