ad. Oil Cons. **Jivisi**on 18**25 N. Franci r.**

Hohhe WM 88240 UNITED STATES Form 3160-5 FORM APPROVED (June 1990) DEPARTMENT OF THE INTERIOR Budget Bureau No. 1004-0135 Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. M MA 600009201 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Well Other WIW-SI 8. Well Name and No. 2. Name of Operator **BLUITT SA 18 FEDERAL #13** PLAINS PETROLEUM OPERTING COMPANY 9. AP! Well No. 3. Address and Telephone No. 30-041-20182 415 W. WALL, SUITE 1000 MIDLAND, TX 79701 915/683-4434 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Bluitt San Andres Associated 660' FSL & 660' FWL, SEC. 18 (M), T8S, R38E 11. County or Parish, State ROOSEVELT, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent X Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Dispose Water (Note: Report results of multi 13. Describe Proposed or Completed Operations (Clearly state all pertinet details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markders and zones pertinent to this work.)* 1) Pressure test 5-1/2" x 2-3/8" casing-tubing annulus to 300 psi. Release Arlington-Elder 5-1/2" x 2-3/8" packer set @ 4583' 2) Circulate hole w/10 ppg mud, POOH & LD all of the 2-3/8" IPC injection tubing and the nickel coated pkr 3,6 3) GIH w/5-1/2" CIBP on WL, set CIBP @ 4600' KBM. Dump 2 sx Prem Plus cmt on top of CIBP 22.25 4) Spot 15 sx Prem Plus cmt from 3000' back to 2050' 5) Perf 5-1/2" csg @ 345' KBM, set pkr on 2-3/8" tbg @ 245'. Establish circulation out of 8-5/8" x 5-1/2" csg annulus w/10 ppg mud. Squeeze w/50 sx Prem Plus cmt. Displace TOC down to 245' Eng play 6) Spot 20 sx Prem Plus from 60' back to surface. Cut off all casings, weld on steel plate across all casings and install dry hole marker 14. I hereby certify that the foregoing is true and correct

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(This space for Federal of State office use)

ADMINISTRATIVE ASSISTANT

·	h <u>i</u> s	
	Received Received	