

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

PERMIT IN TRIPLICATE
(Only instruction for
first copy)

Form approved:
Budget Bureau No. 42-31424

5. LEASE DESIGNATION AND STATE NO.

NM 0520202

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR ROGER HAWKS OIL COMPANY		8. FARM OR LEASE NAME Lone Star	
3. ADDRESS OF OPERATOR c/o Hobbs Pipe & Supply Co., Box 2010, Hobbs, N. M.		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit H, 1680' PNL & 660' FEL		10. FIELD AND POOL, OR WILDCAT S. Prairie Field	
14. PERMIT NO.		15. ELEVATIONS (Show whether DT, ST, CR, etc.)	
		12. COUNTY OR PARISH Roosevelt	
		13. STATE N. M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).*

1. Spot a 25 sx plug at TD to cover all existing perforations.
2. Load hole w/mud-laden fluids.
3. Spot a 35 sx plug at 5-1/2" casing stub.
4. Spot a 50 sx plug in and out of 8-5/8" casing shoe, 5150'-5250'.
5. Spot a 50 sx plug in and out of 8-5/8" casing stub.
6. Spot a 30 sx plug in and out of base of 13-3/8" surface pipe, 400'-500'.
7. Spot a 10 sx plug at top and erect a 4" regulation marker.

AMENDMENT: Spot additional 25 sack cement plugs inside casing at 1000-1100 feet and 2200-2300 feet.

Approval is subject to possible future requirement that pad and/or road be ripped and relevelled.

18. I hereby certify that the foregoing is true and correct

SIGNED S. Saitkin TITLE AGENT DATE 2/27/74

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

FEB 27 1974

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse