

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPL  
(Other instructions  
verse side)

TE-  
re-

Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 05877-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Louise Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 21, T-8-S, R-30-E

12. COUNTY OR PARISH

13. STATE

Roosevelt

New Mexico

1.

OIL WELL ☐ GAS WELL ☐ OTHER Dry Hole

2. NAME OF OPERATOR

SOLAR OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 5596, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)  
At surface

1980' FSL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4110.6 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

It is proposed to plug and abandon as follows:

25 sx over perfs 9684'-9672'  
shoot off 5-1/2" casing @ 8200'.

25 sx plug from 8250'-8150'  
shoot off 8-5/8" casing @ 1500'.

50 sx plug from 1550'-1450'.  
10 sx plug @ surface.

Set marker P&A

AMENDED to specify additional plugs  
and mudding as follows:

1. 25 sx plug 5500-5600'
2. 25 sx plug 4100-4200'
3. 35 sx plug 2200-2300' if 13-3/8" casing is cut and pulled from below 2300 feet.
4. 35 sx plug across shoe of 13-3/8" surface casing.
5. Hole to be filled w/mud between plugs.

18. I hereby certify that the foregoing is true and correct

SIGNED

*M. J. Smith*

TITLE

Production Clerk

DATE

8-12-69

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

AUG 13 1969

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse