

UNITED STATES N. M. OIL CONS. COMM'N
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
PO BOX 1980
HOBBS, NEW MEXICO 88240

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

4M-044216

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Bluitt San Andres Unit

8. FARM OR LEASE NAME

Bluitt San Andres Unit Sec. 13

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Bluitt San Andres Assoc.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 13, T8S, R37E

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

MURPHY OPERATING CORPORATION

3. ADDRESS OF OPERATOR

P. O. Drawer 2648, Roswell, NM 88202-2648

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Unit Ltr. E, 1980' FNL, 660' FWL, Sec. 13, T8S, R37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4007' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

RU PU. Release packer. TOH and lay down packer. SLM in hole w/4-3/4" bit & 8 3-1/8" drill collars w/casing scraper. Drill well out to 4714.3'. Ran cement retainer to 4200'. Set cement retainer at 4673'. Squeeze perfs w/50 sacks Class C 2% CaCl. TOH w/setting tool. PU second cement retainer & SLM back in hole to 4566'. Set retainer and squeeze perfs w/230 sacks Class C 2% CaCl. TIH w/bit to drill. Drill out top retainer and cement to 4668'. TIH w/perforating gun. Perforate 1 JSPF @ 4608, 4609, 4613, 4614, 4618, 4619, 4623, 4627, 4630, 4635, 4636, 4637 (12 holes). TIH w/packer. Set at 4511'. Acidize w/4,000 gals. PAD acid. Drop 24 ball sealers. Well balled off. Flush w/18 bbls. fresh water. Maximum rate - 6.1 BPM, average rate - 3.8 BPM. Maximum pressure - 4,300 psi, average pressure - 2,300 psi. TOH w/packer. TIH w/production string. Install wellhead and begin pumping.

18. I hereby certify that the foregoing is true and correct

SIGNED

Melinda K. Hickman
Melinda K. Hickman

TITLE Production Supervisor

DATE 9-26-88

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
PETER W. CHESTER

DATE

OCT 19 1988

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side