

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other in-
structions on
reverse side)(Form approved.
Budget Bureau No. 42-R355.5.)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

5. LEASE DESIGNATION AND SERIAL NO.

NM-050476

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

SOLSBERY Federal Oil COM

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

TODD - LOWER SAN ANDRES

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

29-7-36 NMPM

12. COUNTY OR
PARISH

ROOSEVELT

13. STATE

N.M.

19. ELEV. CASINGHEAD

-

23. INTERVALS,
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0-TD

-

25. WAS DIRECTIONAL
SURVEY MADE

No

27. WAS WELL CORED

No

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐b. TYPE OF COMPLETION:
NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other ☐

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface

660' FSL x 660' FEL Sec. 29 (P, SE 1/4), T. 29N, R. 7E, S. 36E, N. M.

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED

12-14-69

16. DATE T.D. REACHED

12-20-69

17. DATE COMPL. (Ready to prod.)

12-24-69

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

4137' R. D. B.

20. TOTAL DEPTH, MD & TVD

4363'

21. PLUG, BACK T.D., MD & TVD

4346'

22. IF MULTIPLE COMPL.,
HOW MANY*

-

23. INTERVALS,
DRILLED BY

0-TD

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

4305'-4319' SAN ANDRES

26. TYPE ELECTRIC AND OTHER LOGS RUN

GR-N

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24"	330'	12 1/4"	250 Sx.	
4 1/2"	9.5"	4363'	7 7/8"	300 Sx.	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	4300'	

31. PERFORATION RECORD (Interval, size and number)

4305'-4319' W/2 JSPF

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4305-4319	4000 gal 20% Acid

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
12-25-69		SNAB & FLOW					PRODUCING	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
12-29-69	24	-	→	134	TSTM-NEG NA	0	NA	
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
-	320	→	-	-	-	26.1		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Went - To Be Sold

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE AREA SUPERINTENDENT

DATE DEC 29 1969

*(See Instructions and Spaces for Additional Data on Reverse Side)

mp

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 13: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 32: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
San Andres	4305	4319	Oil & Gas Prod. Zone

38. GEOLOGIC MARKERS

NAME	MEAS. DEPTH	TRUE VERT. DEPTH
YATES	2405	
QUEEN	3017	
SAN AND	3556	