

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other Instructions on
reverse side)

Form approved.
Budget Bureau No. 42 R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1983-05-15-476
DEC 22 11 42 AM '83
CASE DESIGNATION AND SERIAL NO.
INDIAN, ALLOTTEE OR TRIBE NAME

1. WELL OIL WELL ☒ GAS WELL ☐ OTHER <u>DRL WELL</u>	7. UNIT AGREEMENT NAME <u>SOLSBERY FEDERAL OIL COM</u>
2. NAME OF OPERATOR <u>PAN AMERICAN PETROLEUM CORPORATION</u>	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR <u>BOX 68, HOBBS, N. M. 88240</u>	9. WELL NO. <u>1</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>660' FSL x 660' FEL SEC 29 (Und P, SE 1/4 SE 1/4)</u>	10. FIELD AND POOL, OR WILDCAT <u>TODD -</u>
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>29-7-36 NMPM</u>
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH <u>ROOSEVELT</u>
	13. STATE <u>N.M.</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) <u>Spudding</u> ☒	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

*Card Drilg Co. spudded 12 1/4" hole 8:30 AM 12-14-69.
At 1:PM 8 5/8" OD 24" J-55 casing was set @ 330'
w/ 250 SX Incon 2% Gel. Cement Circ. After 18 hours,
tested casing w/ 1200 PSI for 30 min. Test O.K.
Reduced hole to 7 7/8" @ 330' and resumed drilling.*

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE AREA SUPERINTENDENT

DATE DEC 16 1969

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

*DN-4-UGGS-11
1-MSO
1-SSP
1-REV
1-Featherstone*

TITLE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

DEC 17 1969

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO