

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-041698-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Kirkpatrick Federal

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Bluitt San Andres Assoc.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 14, T8S, R37E

12. COUNTY OR PARISH 13. STATE

Roosevelt

New Mexico

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Eugene E. Nearburg

3. ADDRESS OF OPERATOR

3303 Lee Parkway, Dallas, Texas 75219

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980' FSL and 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4016.4 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Plug Back ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Pulled tubing and set retainer at 4530'. Squeezed perforations 4611' - 57' (14 holes) with 200 sacks cement. Drilled out to 4758'. Perforated @ 4638' and 4654' with 1 shot (2 holes). Acidized with 500 gallons 15% acid. Acidized with 8000 gallons 15% acid.

Set retainer at 4605'. Squeezed perfoations with 100 sacks cement. Perforated 7 holes as follows: 4518', 4520', 4558', 4564', 4568', 4573' and 4579'. Acidized with 500 gallons 15% acid. Acidized with 5000 gallons 15% acid and 8 ball sealers.

18. I hereby certify that the foregoing is true and correct

SIGNED

James B. [Signature]

TITLE Petroleum Engineer

DATE 5-13-70

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

MAY 19 1970

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side