INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Ŗ

Northwestern New Mexico

i

-	Anhy	1875	т	Canvon	T.	Ojo Alamo	Т.	Penn. "B"
	F -14		т	Strawn	T.	Kirtland-Fruitland	Т.	Penn. "C"
			T	Atolco	т	Pictured Cliffs	1. L	Penn. "D"
-	. .	2616	т	Miss	Т.	Cliff House	Т.	Leadville
т.	Yates	2010	т. Т	Devonian	Т.	Menefee	Т.	Madison
-	0		т	Silurian	т.	Point Lookout	Т.	Elbert
~	0 1 1		т	Montova	Т.	Mancos	Т.	McCracken
1. T	Grayburg	3845	T		Т.	Gallup	Т.	Ignacio Qtzte
1. T	San Andres	5218	T		. Bas	se Greenhorn	Т.	Granite
т.	Glorieta		. т. т	Ellenburger	T.	Dakota	Т.	
Т. 			. т. т	Gr Wash	т.	Morrison	т.	
Т. т	Blinebry	6650	- 1. T	Granite	. Т.	Todilto	т.	·
1.	Tubb		- 1. T	Delaware Sand	т.	Entrada	т.	
		7175	т	Dono Springs	- T.	Wingate	. Т.	·
		0516	m		т	Chinle	. Т.	
			m		т	Permian	- T.	
т.	Penn	0222	- 1. ~~		- т. т	Penn. "A"	. [.] Т.	
т	Cisco (Bough C) -	7737	- I.					

FORMATION RECORD (Attach additional sheets if necessary)

From	То	Thickness in Feet	Formation	From	Τo	Thickness in Feet	Formation
	2616 2740 3845 5218 5310 7475 8000 8516	741 124 1105 1373 92 2165 1525 516	Dolomite, sand, shale Dolomite & Lime Sand Dolomite, Lime, Sand Shale & Dolomite Dolomite & Sand		1		
8516	9365	849	Lime & Shale				

REELEVED

MAY 2 1070 OIL CONCERNITION COMM. North Line