

| | | |
|------------------------|--|--|
| NO. OF COPIES RECEIVED | | |
| DISTRIBUTION | | |
| SANTA FE | | |
| FILE | | |
| U.S.G.S. | | |
| LAND OFFICE | | |
| OPERATOR | | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| |
|--|
| 5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/> |
| 5. State Oil & Gas Lease No. K-3582 |
| 7. Unit Agreement Name |
| 8. Farm or Lease Name Gates State |
| 9. Well No. 3 |
| 10. Field and Pool, or Wildcat Todd Lower San Andres |
| 12. County Roosevelt |

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| |
|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> |
| 2. Name of Operator FRANKLIN, ASTON & FAIR, INC. |
| 3. Address of Operator P. O. Box 1090, Roswell, New Mexico 88201 |
| 4. Location of Well UNIT LETTER F , 1830 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 32 m TOWNSHIP 7S RANGE 36E NMPM. |

15. Elevation (Show whether DF, RT, GR, etc.)

4117' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

| | |
|--|---|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | OTHER <input type="checkbox"/> |

SUBSEQUENT REPORT OF:

| | |
|--|---|
| REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> | OTHER <input type="checkbox"/> |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On March 26, 1970, set 4½" J55 9.5# csg. at 4338' KB using 300 sacks Incor Poz cement 2% gel with 8# salt per sack. On April 1, 1970, pressured upon csg. to 800 psi and held for 30 minutes, pressure held cement job okay. Cementing work done by Halliburton.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

| | | |
|--|----------------------------------|---------------------|
| SIGNED <u><i>Grant M. Smith</i></u> | TITLE <u>Geologist</u> | DATE <u>4-14-70</u> |
| APPROVED BY <u><i>Joe J. [Signature]</i></u> | TITLE <u>SUPERVISOR DISTRICT</u> | DATE <u>4-22-70</u> |
| CONDITIONS OF APPROVAL, IF ANY: | | |