

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
L-528

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry	7. Unit Agreement Name
2. Name of Operator FRANKLIN, ASTON & FAIR, INC.	8. Farm or Lease Name Lyle State
3. Address of Operator P. O. Box 1090, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 33 TOWNSHIP 7S RANGE 36E NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 4117.82' GR	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well was drilled to a total depth of 4410' and 4 1/2" casing was set at T.D. using 300 sx cement. The Slaughter "B" zone was perforated at 4368-4382' and acidized with 2500 gallons, swabbed dry; perforated at 4390-4398' and acidized with 2500 gallons, swabbed dry. It is our intention to plug and abandon this well as follows: Spot 25-sack cement plug across perfs 4368-4398' through tubing. Run free-point and shoot 4 1/2" casing and spot a 25-sack cement plug at or near top of San Andres at 3575' through casing. A 25-sack plug will be spotted at the base of the salt at 2100-2200'. A 25-sack cement plug will be spotted in and out of the 8 5/8" casing at 294' and a 10-foot plug and marker will be set at surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Grant M. Smith</u>	TITLE <u>Geologist</u>	DATE <u>June 30, 1970</u>
APPROVED BY <u>Joe D. Haney</u>	TITLE <u>SUPERVISOR DISTRICT</u>	DATE <u>JUL 2 1970</u>
CONDITIONS OF APPROVAL, IF ANY:		

25 sx @ top salt