

July 1968)

DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM 4039-A
2. NAME OF OPERATOR Roger C. Hanks		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 2000 Wilco Building, Midland, Texas 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL & 1980' FWL, Sec. 34-8S-35E		8. FARM OR LEASE NAME Peggy Federal
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4179.6 GR		10. FIELD AND POOL, OR WILDCAT Vada Pennsylvanian
		11. SEC. T., R., M.; OR BLK. AND SURVEY OR AREA 34-8S-35E
		12. COUNTY OR PARISH Roosevelt
		13. STATE N.Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Spud, Set Surf & Inter. ☒	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-9-70 Spudded 17 1/2" hole at 12:00 noon. Ran 10 joints of 12 3/4" 42# casing. Set & cemented at 417' with 400 sx. Class H, 2% Calcium Chloride. Plug down at 8:00 p.m. Cement circulated. WOC 24 hours. Tested 750# for 30 min. Tested okay.

6-15-70 Depth 4050'. Ran 105 joints of 8 5/8" 32# & 24# casing. Set & cemented at 4050' with 35 sx. Class C, 2% Calcium Chloride. Plug down at 11:00 a.m. WOC 24 hours. Tested 750# for 30 min. Tested okay.

18. I hereby certify that the foregoing is true and correct

SIGNED Roger C. Hanks TITLE Operator

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD

JUN 19 1970

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

JUN 23 1970

U.S. DEPARTMENT OF JUSTICE
FEDERAL BUREAU OF INVESTIGATION
WASHINGTON, D.C. 20535