

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIP  
(Other instructions  
verse side)DE-  
reForm approved  
Budget Bureau No. 1-4-1

5. LEASE DESIGNATION AND SURVEY OR AREA

NM-6871

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Fran-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR B.L.E. AND  
SURVEY OR AREA33-8-31  
25-8S-36W

12. COUNTY OR PARISH 13. STATE

Roosevelt

N. M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Roger C. Hanks

3. ADDRESS OF OPERATOR

c/o Hobbs Pipe &amp; Supply, Box 2010, Hobbs, N. M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

Unit H, 1980' TNL &amp; 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☒CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The following work to be done for plugging &amp; abandonment:

1. Ran a cast iron bridge plug to cover existing perforations, and dump 30' of cement on top.
2. Load hole w/mud-laden fluids.
3. Spot a 100' plug at stub of 5-1/2" casing.
4. Spot a 100' plug in and out of intermediate casing set at 4,015'.
5. Spot a 100' plug at top of salt, if intermediate casing is recovered from below this depth.
6. Spot a 100' plug in and out of stub of 8-5/8" casing.
7. Spot a 100' plug in and out of base of surface casing set at 405'.
8. Spot a 10 sx top-hole plug and erect a 4" regulation marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

3/7/74

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAR 7 1974

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side