

COUNTY ROOSEVELT FIELD Wildcat STATE NM 30-041-20313

OPR UNION OIL CO. OF CALIFORNIA MAP

1. State "A-36"

Sec 36, T-7-S, R-36-E

CO-ORD

660' FSL, 660' FWL of Sec

Spd 2-27-71

CLASS

EL 4100²

Cmp 5-8-71

CSG & SX TUBING

8 5/8" at 366' w/175 sx

4 1/2" at 4705' w/500 sx.

FORMATION	DATUM	FORMATION	DATUM

LOGS EL GR RA IND HC A

TD 4705'

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Logging Service, Inc.

CONT. Verna

PROP DEPTH 5000' TYPE RT

DATE

3-2-71 F.R. 3-2-71; Opr's Elev. 4090' GL
3-8-71 PD 5000' RT (San Andres)
3-22-71 Contractor - Verna
3-29-71 Drlg. 485'
Drlg. 4610'
TD 4705' (Tight)
TD 4705'; PBD 4575'; Prep Acid
No Tests or Cores
Perf 4667-71' w/2 SPF
Acid (4667-71') 250 gals
Swbd 10 BLO + 70 BW in 2 hrs 45 mins (4667-71')
Sqzd (4667-71') w/125 sx
Perf 4654-57' w/2 SPF
Acid (4654-57') 500 gals

3-29-71

Continued

Swbd 14 BLO + 12 BAW + 80 B salt wtr in
3 hrs 15 mins (4654-57')

BP @ 4633'

Perf 4585-87', 4589-93', 4597-4603' w/2 SPF

Acid (4585-4603') 1000 gals

Swbd 1 BLO + 3 BAW in 45 mins (4585-4603')

Did not recover load

BP @ 4575'

Spotted 250 gals acid

Perf 4548-66' w/1 SPF

Swbd 3 BO + 1 BAW in 30 mins (4548-66')

4-5-71

TD 4705'; PBD 4575'; Ppg load

Acid (4548-66') 1000 gals

Swbd 1½ BO + 5 BAW in 4 hrs + gas @ 43.7

4-5-71

Continued

MCFGPD (4548-66')

Acid (4548-66') 500 gals

Frac (4548-66') 40,000 gals wtr + 58,500# sd

Ppd 65 BLW in 24 hrs (4548-66') (-680 BLW)

4-12-71

TD 4705'; PBD 4575'; Ppg load (-368 BLW)

4-19-71

TD 4705'; PBD 4575'; TO Pmp

Ppd 1 BO + 17 BLW in 24 hrs (4548-66')

4-26-71

TD 4705'; PBD 4571'; SI

5-3-71

TD 4705'; PBD 4571'; TO Pmp

Ppd 1 BO + 21 BFW + gas @ 83 MCFGPD in 24 hrs
(4548-66')

5-10-71

TD 4705'; P&A (Holding for Tops)

5-17-71

TD 4705'; PLUGGED & ABANDONED

LOG TOPS: Anhydrite 2307', San Andres 3815',
Milnesand 4521'

5-20-71

COMPLETION REPORTED