

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLE
(Other Instructions
on reverse side)TE
FOForm approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-016663

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H.E. Roelofs Federal MCT-1

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Todd Wolfcamp

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 21, T-7-S, R-35-E

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. WELL TYPE
OIL ☒ GAS ☐
WELL ☐ OTHER ☐

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P.O. Box 728 - Hobbs, New Mexico 88240

4. LOCATION OF WELL. Report location clearly and in accordance with any State requirements.
(See also space 17 below.)Well is located 1920' from the South Line and 1980' from the
East Line of Sec. 21, T-7-S, R-35-E, Unit Letter J.

14. PERMIT NO.

Regular

15. ELEVATIONS (Indicate whether DE, BT, OR, etc.)

4229' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

WELL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Give fully state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

TOTAL DEPTH 350'

Spudded 15" hole May 7, 1971

Ran 334' (9 Joints) 11-3/4" OD 42# H-40 casing and cemented at 350' with 380 sxs. Class C
cement w/1% CaCl. Plug at 320'. Cement circulated. Job complete 4:00 P.M., May 7, 1971.Tested 11-3/4" OD casing for 30 minutes from 10:00 A.M. to 10:30 A.M., May 8, 1971 with 600#.
Tested O.K. Drilled out cement plug and re-tested for 30 minutes with 600# from 11:00 to
11:30 A.M., May 8, 1971. Tested O.K. Job complete 11:30 A.M., May 8, 1971.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Assistant District
Superintendent

DATE

May 10, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO