SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION C-102 and C-103 Effective 1-1-65 Sa. Indicate Type of Lease State X Fee State X Fee 5. State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLS CO NOT USE THIS FORM FOR PROPOSALS TO SHILL OR TO DLEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. COIL X GAS WELL X GAS WELL COILER- 7. Unit Agreement Name	NO. OF COPIES RECEIVED	,	Form C-103 Supersedes Old
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS STATE "CO" STAT			
U.S. DEPTICE OPERATOR SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS OF A SUNDRY NOTICES AND REPORTS ON WELLS The Supplement of the Sundry Notice of the		NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS CHIES SERVICE OIL COMPANY STATE "CO" STATE "CO" STATE "CO" STATE "CO" STATE "CO" SUNDRY NOTICES AND REPORTS ON WELLS STATE "CO" SUBSCOURT REPORT OF COMPANY SUBSCOURT REPORT OF COMPANY SUBSCOURT REPORT OF: SUBSCOURT REPORT OF:		 	5g. Indicate Type of Lease
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS CITIES SERVICE OIL COMPANY CITIES SERVICE OIL COMPANY P.O. 30X 69, H0035, NEW MEXICO 83240 SOUTH THE ASS. SACE 30E L 1980 SOUTH THE ASS. SACE 30E NOTICE OF INTENTION TO Check Appropriate Box In Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO TENTION TO ASS. SACE OIL COMPANY CHECK APPROPRIATE BOX In Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO THE ASS. SACE SHIPS COMPANY OF EACH FIRST. TO 450 Red Bed. Spudded 12½th hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 Joints 8 5/8th OD 24# J-55 & K-55 casing. Set at 449 feet and comented with 300 sax Class C W/2%. Calcium chloride. Plug down at 1:35 A.M. 7-23-71. Circulated 50 sax cement to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling ahead.			
SUNDRY NOTICES AND REPORTS ON WELLS A CONTROL OF STATE VICE OF LOURS AND REPORTS ON WELLS TO THE SERVICE OIL COMPANY STATE VICE 1. SHARM AND	-		
To Unit Agreement Name CITIES SERVICE OIL COMPANY STATE "CO" SATE "CO" SUMIN P.O. 30X 69, H0885, NEW MEXICO 88240 10. Field and Pool, or Bildon 10. Field and Pool, or Bildon SUMIN See For E. R. C. R. etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO SUBSEQUENT REPORT OF: Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO SUBSEQUENT REPORT OF: Continue Substantian above in the Annual Accessory of Printense density, and give portained dates, including estimated dates of stating any proposed winds) SEE RULE 1955. To 450 Red Bed. Special 124" hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 joints 8 5/8" OO 24# J-55 & K-55 casing. Set at 449 feet and commented with 300 sax Class C W/2%. Calclum chloride. Plug down at 1:35 A,M. 7-28-71. Circuit ated 50 sax cament to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling shead.	OPERATOR		
CITIES SERVICE OIL COMPANY CITIES SERVICE OIL COMPANY STATE "CO" O. WEIDE P.O. 805 459, 40035, NEW MEXICO 88240 I. Pleid and Fool, or Wildows The MEST The service 16 To Toke Service 16 Toke Service 17 Toke Service 16 Toke Service 17 Toke Service 16 Toke Service 17	SU SEC NOT USE THIS FORM F	INDRY NOTICES AND REPORTS ON WELLS PROPOSALS TO SHILL OR TO DEEPEN OF PLUG BACK TO A DIFFERENT RESERVOIR. PROPOSALS TO SHILL OR TO DEEPEN OF SUCH PROPOSALS.	
STATE "CCI" CHTES SERVICE OIL COMPANY STATE "CCI" SATE "CCI" S	l. GAS	23.452	7. Unit Agreement Name
P.O. 305 69, H083S, NEW MEXICO 88240 10. Field and Fool, or Wildow 11. Field and Fool, or Wildow 12. Causery 13. Causery 14. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: 15. Causery 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: 17. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: 17. Check Appropriate East Appropriate Converted Balance Of Surviva Conver	2. Make of Operator		1
P.O. 30X 69, H083S, NEW MEXICO 83240 11. Field and Pool, or Wildows 12. Foreign of Mexico 13. Foreign of Mexico 14. Field and Pool, or Wildows 15. Field and Pool, or Wildows 16. Field and Pool, or Wildows 17. Field and Pool, or Wildows 18. Field		L COMPANY	
THE WEST INC. SECTION 15 CANNOT BE ASSOCIATED BY THE MEAN SUB- SECTION 15 CANNOT BE ASSOCIATED BY A SECTION 15 CANNOT BE ASSOCIATED BY A SECTION BY	P.O. BOX 69, HOBB	S, NEW MEXICO 88240	1
WEST 100. 150 160 180 180 180 180 180 180 180 180 180 18			
Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: REMEDIAL ADAR SUBSEQUENT REPORT OF: REMEDIAL ADAR SUBSEQUEN	UNIT CETTER	. 1980 FEST PROVIDED SOUTH LINE AND 560 FEET PRI	"minimum"
Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: REMEDIAL ADAR SUBSEQUENT REPORT OF: REMEDIAL ADAR SUBSEQUEN	THE WEST DINE.	SECTION 16 TOWNSHIP 85 HANGE 38E NIMP	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: **REFORM SECURIAL MORE **PLUG AND ABANDON** **PLUG AND	- 484		
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: DESTORM REMEDIAL NORM TEMPORATION AGAING TEMPORATION AGAING TEMPORATION AGAING TEMPORATION AGAING TEMPORATION AGAING TEMPORATION AGAING TO THER TO		.*. Flow dron. (Show whether DF, RT, GR, etc.)	
SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: SUBSE		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Rooseveit /////////
PLUG AND ABANDON PULL OR ALTER CASING CHARGE CASING COMPILE TO A STATE CASING CASING TEST AND CEMENT JOB XX TO HAVE CASING TO THE MILLING OPES. TO 450 Red Bed. Spudded 12½" hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 joints 8 5/8" OD 24# J-55 & K-55 casing. Set at 449 feet and cemented with 300 sax Class C W/2% Calcium chloride. Plug down at 1:35 A.M. 7-23-71. Circulated 50 sax cement to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling ahead.		• •	
TD 450 Red Bed. Spudded 12½ hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 joints 8 5/8" OD 24# J-55 & K-55 casing. Set at 449 feet and cemented with 300 sax Class C W/2% Calclum chloride. Plug down at 1:35 A.M. 7-23-71. Circulated 50 sax cement to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling ahead.	NOTICE	OF INTENTION TO: SUBSEQUEN	IT REPORT OF:
TD 450 Red Bed. Spudded 12½ hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 joints 8 5/8" OD 24# J-55 & K-55 casing. Set at 449 feet and cemented with 300 sax Class C W/2% Calclum chloride. Plug down at 1:35 A.M. 7-23-71. Circulated 50 sax cement to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling ahead.		3 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 -	ALTERNA GAGINA
TD 450 Red Bed. Spudded 124" hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 joints 8 5/8" OD 24# J-55 & K-55 casing. Set at 449 feet and cemented with 300 sax Class C W/2% Calcium chloride. Plug down at 1:35 A.M. 7-28-71. Circulated 50 sax cement to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling ahead.		——————————————————————————————————————	
TD 450 Red Bed. Spudded 12½" hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 joints 8 5/8" OD 2½# J-55 & K-55 casing. Set at 449 feet and cemented with 300 sax Class C W/2% Calcium chloride. Plug down at 1:35 A.M. 7-28-71. Circulated 50 sax cement to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling ahead.			PLUG AND ABANDONMENT
TD 450 Red Bed. Spudded 12½ hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 joints 8 5/8 OD 24# J-55 & K-55 casing. Set at 449 feet and cemented with 300 sax class C W/2% Calcium chloride. Plug down at 1:35 A.M. 7-28-71. Circulated 50 sax cement to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling ahead. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	PULL OR ALTER CASING		
TD 450 Red Bed. Spudded 12½ hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 joints 8 5/8" 00 24# J-55 & K-55 casing. Set at 449 feet and cemented with 300 sax Class C W/2% Calcium chloride. Plug down at 1:35 A.M. 7-28-71. Circulated 50 sax cement to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling ahead. 18. Thereby certify that the information above is true and complete to the best of my knowledge and belief. 19. The District Admin. Supervisor Date July 29, 1971	OTHER		
TD 450 Red Bed. Spudded 12½" hole at 5:30 P.M. 7-27-71 and drilled to TD of 450 feet. Ran 15 joints 8 5/8" OD 24# J-55 & K-55 casing. Set at 449 feet and cemented with 300 sax Class C W/2% Calcium chloride. Plug down at 1:35 A.M. 7-28-71. Circulated 50 sax cement to pit. WOC 24 hours. Tested casing to 1000 psi for 30 minutes. Held okay. Drilling ahead. 18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.			
TITLE District Admin, Supervisor DATE July 29, 1971	Spudded 121 hole OD 24# J-55 & K-5 Calcium chloride. WOC 24 hours. Te	5 casing. Set at 449 feet and cemented with 300 s Plug down at 1:35 A.M. 7-28-71. Circulated 50 s sted casing to 1000 psi for 30 minutes. Held okay	ax Class C W/2% ax cement to pit.
2.40 (2.4/3 3 1	18. I hereby certify that the infor		
APPROVED BY ALCOHOLD TITLE DISTRICT I DATE AUG 2 1971	SIGNED	TITLE District Admin, Supervis	
APPROVED BY TITLE DATE	0 -	to passent in the property of the passent of the pa	TI AUG 2 1971
	APPROVED BY	Colffee TITLE	DATE