orm 3160-5 June 1990)	DEPARTMENT	ED STATES OF THE INTERIOR AND MANAGEMENT	en un stons () A Steer Cont Steer	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals				NM-94121 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE				7. If Unit or CA, Agreement Designation
1. Type of Well Oil Well Well Other Other				<ol> <li>8. Well Name and No. Gates-O'Brien "27" Fed</li> <li>9. API Well No.</li> <li>10. Field and Pool, or Exploratory Area</li> </ol>
2. Name of Operator OGS Operating Company, Inc.				
3 Address and Telephone No. 550 W. Texas, Suite 1140; Midland, Texas 79701 (915)682-6373				
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Todd Upper San Andres
(K) 1980' FSL & 1980' FWL Sec. 27, T-7-S, R-35-E			11. County or Parish, State Roosevelt, New Mexico	
CHECK	APPROPRIATE BOX(s	) TO INDICATE NATURE	OF NOTICE, REPO	DRT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION			<u> </u>	
Image: Subsequent Report         Image: Final Abandonment Notice		Abandonment Recompletion Plugging Back Casing Repair Altering Casing		Change of Plans  New Construction  Non-Routine Fracturing  Water Shut-Off Conversion to Injection
		Other		Note: Report results of multiple completion on Well (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
give subsurface loci OGS Oper	ations and measured and true vertica	pertinent details, and give pertinent dates, I depths for all markers and zones pertir . has plugged and aba	ient to this work.)*	
give subsurface loc: OGS Oper "27" Fec Plug # Plug # Plug # Plug # Plug #	ations and measured and true vertica rating Company, Inc # #1 as follows: #1 CIBP Set @ 4123 4 1/2" casing @ #2 50 sx 3610'-34 #3 40 sx 2212'-20 #4 40 sx 380'-230 #5 20 sx 30'-0'	d depths for all markers and zones pertir . has plugged and aba 5' cap w/2 sx cement. cut and pulled @ 3579 417' Tagged plug @ 3 060' (1-29-97) 0' (1-29-97) (1-29-97)	ent to this work.)* Indoned the Gates ' (1-27-97) 380' (1-29-97)	
give subsurface loc: OGS Oper "27" Fec Plug # Plug # Plug # Plug # Plug #	ations and measured and true vertica rating Company, Inc # #1 as follows: #1 CIBP Set @ 4123 4 1/2" casing @ #2 50 sx 3610'-34 #3 40 sx 2212'-20 #4 40 sx 380'-230 #5 20 sx 30'-0'	d depths for all markers and zones pertir . has plugged and aba 5' cap w/2 sx cement. cut and pulled @ 3579 417' Tagged plug @ 3 060' (1-29-97) 0' (1-29-97)	ent to this work.)* Indoned the Gates ' (1-27-97) 380' (1-29-97)	
give subsurface loc: OGS Oper "27" Fec Plug # Plug # Plug # Plug # Plug #	ations and measured and true vertica rating Company, Inc # #1 as follows: #1 CIBP Set @ 4123 4 1/2" casing @ #2 50 sx 3610'-34 #3 40 sx 2212'-20 #4 40 sx 380'-230 #5 20 sx 30'-0'	d depths for all markers and zones pertir . has plugged and aba 5' cap w/2 sx cement. cut and pulled @ 3579 417' Tagged plug @ 3 060' (1-29-97) 0' (1-29-97) (1-29-97)	ent to this work.)* Indoned the Gates ' (1-27-97) 380' (1-29-97)	
give subsurface loca OGS Oper "27" Fec Plug # Plug # Plug # Plug # Cut of	ations and measured and true vertica rating Company, Inc # #1 as follows: #1 CIBP Set @ 4124 4 1/2" casing @ #2 50 sx 3610'-34 #3 40 sx 2212'-20 #4 40 sx 380'-230 #5 20 sx 30'-0' Ef well head and in e foregoing is true and correct	depths for all markers and zones pertir . has plugged and aba 5' cap w/2 sx cement. cut and pulled @ 3579 417' Tagged plug @ 3 060' (1-29-97) 0' (1-29-97) (1-29-97) (1-29-97) stalled dry hole mark	ent to this work.)* Indoned the Gates ' (1-27-97) 380' (1-29-97)	
give subsurface locs OGS Oper "27" Fec Plug # Plug # Plug # Plug # Cut of	ations and measured and true vertica rating Company, Inc # #1 as follows: #1 CIBP Set @ 412! 4 1/2" casing of #2 50 sx 3610'-3. #3 40 sx 2212'-2. #4 40 sx 380'-23. #5 20 sx 30'-0' Ef well head and in the foregoing is true and correct	d depths for all markers and zones pertir . has plugged and aba 5' cap w/2 sx cement. cut and pulled @ 3579 417' Tagged plug @ 3 060' (1-29-97) 0' (1-29-97) (1-29-97) (1-29-97) stalled dry hole mark 	<pre>ent to this work.)* indoned the Gates ' (1-27-97) 380' (1-29-97) cer. Fight 1/99, </pre>	

-V

dos