

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Ted Weiner Oil Properties and Century Petroleum Ltd.		8. Farm or Lease Name A. E. Lewis
3. Address of Operator 1616 Oil and Gas Building, Fort Worth, Texas 76102		9. Well No. 1
4. Location of Well UNIT LETTER B , 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 8 TOWNSHIP 8S RANGE 38E NMPM.		10. Field and Pool, or Wildcat Bluitt San Andres Assoc.
15. Elevation (Show whether DF, RT, GR, etc.) 3980.8 GR		12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/20/72 Spudded well, drilled to 350', ran 8 5/8" 20# surface casing and set with 225 sacks Class H cement W/2% cc @ 350', circulated & WOC 24 hours.


9/29/72 Drilled to TD 4769', ran DST #1 from 4730' to 4769', recovered 60' of vsogcmud

9/30/72 Drilled on to TD 4800', ran logs, temp. abandoned well by welding cap on surface casing, released rig.

1/23/73 Advised Oil Conservation Commission of decision not to complete well and requested advise for plugging procedure.

1/29/73 Received instructions in letter to set plugs as follows, and advise 24 hours before work is to be done.
100' Cement plug at 4800'
100' plug at top of San Andres
100' plug at base of Salt
100' plug at top of Salt
100' plug 1/2 in and 1/2 out of surface pipe @350'
10 sack plug at surface of hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 	TITLE Petroleum Engineer	DATE April 2, 1973
APPROVED BY Joe D. Ramey	TITLE	DATE APR 9 1973
CONDITIONS OF APPROVAL, IF ANY		