

- 1-16,17,18: POH, ran csg gun to 4495', ran bit to 4500', drld cmt 4500/4625, circ hole cln, POH, perf 4590', ran tbg & pkr to 4350', could not pump in w/4000**, set pkr 4580', spot 250 gal acid BDP 2500, reset pkr 4350', sqzd perf @ 4590' w/100 sks, rlsd pkr, POH, drld cmt 4455/4590' & 4718/4740', circ hole clean.
- 1-19,20: POH, perf 4690/4710' & 4600/4620' w/1 JSP2F w/4" csg gun, ran tbg, RBP & pkr, acdz perfs 4690/4710' w/1000 gals, reset RBP @ 4657', ACDZ perfs 4600/4620' w/1000 gals, reset RBP @ 4724', set pkr @ 4535'.
- 1-20,21,22: Crews off due to weather.
- 1-23: Swbd 8 1/2 hrs, rec trace oil, 101 BLAW
- 1-24; Swbd 5 hrs, rec 1/2 B0, 59 BLAW
- 1-25,26: Swbd 5 hrs, rec trace oil, 56 BW, FL 3600 to 4300', rlsd pkr, POH, WIH w/2 7/8" tbg to 4715, ND BOP, NU wellhead, ran rods, rlsd rig.
- 1-27: Well TA pending further study and evaluation

1-27-80

RECEIVED

MAR 8 1976

OIL CONSERVATION COMM.
HOBBS, N. M.