

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N.M. - 11140

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Blockson-Federal

9. WELL NO.

- 1

10. FIELD AND POOL, OR WILDCAT

Vada Penn

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 34, T-8-S, R-34-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ST, GR, etc.)

GR. - 4258.7

12. COUNTY OR PARISH

Roosevelt

13. STATE

N. Mexico

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. 9-20-72 - Set 13-3/8" csg. Ran 405.10', 14 jts., 13-3/8", 48.0# Youngstown Grade "H" csg., and 1.90' 13-3/8" Howco cement guide shoe. Howco baffle plate @ 407'. Cemented w/420 sxs. Class "C" cement w/2% Calcium Chloride & T/4#/sxs. Flocele. Circulated approx. 150 sxs. WOC 18 hours. Pressure tested csg. @ 600# for 30 minutes. Tested O.K. Casing seat at 420'.

2. Drilling

18. I hereby certify that the foregoing is true and correct

SIGNED

*Charles Gray*

TITLE

Proration Clerk

DATE

9-25-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side