

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO
SUBMIT IN TRIPLIC
(Other instructions o
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. NM-0408232
2. NAME OF OPERATOR MWJ PRODUCING COMPANY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 413 FIRST NATIONAL BANK BUILDING, MIDLAND, TEXAS 79701	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FEL & 1980' FSL of Sec. 7, T-8S, R-38E, NMPM	8. FARM OR LEASE NAME USA
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	10. FIELD AND POOL, OR WILDCAT BLEITT, SAN ANDRES
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 7, T-8S, R-38E
	12. COUNTY OR PARISH ROOSEVELT
	13. STATE NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☒
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

WELL PLUGGED AND ABANDONED

- 1) Drilled 10-3/4" hole to 370', set 8-5/8" and cemented w/300 sx of Class "H" w/2% CaCl₂.
- 2) Drilled 7-7/8" hole to 4772, using 10.0#/gal. mud.
- 3) Ran Schlumberger sidewall neutron porosity log from 4772' to surface.
- 4) Spotted Class "H" cement plugs at the following depths:
 - a) Top of San Andres porosity 4100', cement plug 4100' to 3980'.
 - b) Top of Yates 2680', cement plug 2700' to 2580'.
 - c) Top of Anhydrite 2370', cement plug 2400' to 2280'.
 - d) Bottom of surface casing 370', cement plug 420' to 300'
 - e) Surface plug 0' to 20'. **INSTALLED DRY HOLE MARKER.**10.0 #/gal drilling mud was left in the hole between all plugs.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. L. Felt
R. L. Felt

TITLE **Agent**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED
DEC 17 1973

ARTHUR R. BROWN
DISTRICT ENGINEER

DATE

12/13/72

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.