

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 056 0261

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER Dry hole

2. NAME OF OPERATOR

The Desana Corporation

3. ADDRESS OF OPERATOR

610 Vaughn Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

766' FNL & 1874' FWL of Section 8, T-8-S, R-38-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3995.1 GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 8

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Bluitt (S.A.) Assoc.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 8

T-8-S, R-38-E

12. COUNTY OR PARISH

13. STATE

Roosevelt

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

PLUGGING PROCEDURE:

Hole loaded w/10.0 PPG Salt Gel Laden Fluid.

Spotted cement plugs as follows:

1. 35 sx Cement 4563' to 4700'
2. 35 sx Cement 2663' to 2800'
3. 35 sx Cement 1863' to 2000'
4. 35 sx Cement 293' to 430' (In & out of bottom of surface casing)
5. 10 sx Cement to surface. 4" pipe, standing 4' above surface, was placed in surface plug. Dry Hole marker had bead on side of pipe "L-8-8-38"

Cleaned Location 3-27-74

BTA ON OR ABOUT 3-25-74

18. I hereby certify that the foregoing is true and correct

SIGNED Tom R. Cook

TITLE Production Superintendent DATE April 1, 1974

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

*See Instructions on Reverse Side

APPROVED
OCT 1 1974
ARTHUR R. BROWN
DISTRICT ENGINEER