

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI
(Other instructions
verse side) RE-Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. NM-0497735
2. NAME OF OPERATOR Texaco Inc.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 728 Hobbs, New Mexico 88240	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1815' FSL & 1815' FWL, Sec. 26, T-7S, R-35E	8. FARM OR LEASE NAME M A Cunningham NCT-1
14. PERMIT NO. Reg.	9. WELL NO. 2
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4183' GR	10. FIELD AND POOL, OR WILDCAT Todd Wolfcamp
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 26, T-7S, R-35E
	12. COUNTY OR PARISH Roosevelt
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐**Csg Test & Cmt Job** ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 7750'
3490' (82 jts) 8 5/8' csg set @ 3500'
Ran 4521' (113 jts) 5 1/2' liner & set @ 7750'. Hung in 8 5/8' csg @ 3214'.
Cemented w/25 sx Class C cmt, 1400 sx TLW, followed w/200 sx Class C cmt
all mixed w/.4% Halid 22 & 4% salt/sx. Preceded cmt w/1250 gals mud
flush.
Plug down 6:45 a.m. 9-20-74
Ran 8 5/8' pkr & set @ 3076'.
Squeezed top of liner @ 3216' w/50 sx LWL
cement followed w/100 sx Class C cmt. to 2100#.
Preceded cmt w/250 gals mud flush.
Pulled pkr
Tested 8 5/8' csg 1000# 11:15 to 11:45 a.m. 9-29-74
Tested OK
Ran bit to 7216. DOC 7216 - 7675'.
Tested 5 1/2' liner & 8 5/8' csg @ 12:15 - 12:45 a.m. 9-30-74 to 1500#. Tested OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE **Asst. Dist. Supt.**DATE **9-23-74**

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
OCT 18 1974
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

947 - 485

