

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	5. LEASE DESIGNATION AND SERIAL NO. NM 683
2. NAME OF OPERATOR Coquina Oil Corporation	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Drawer 2960, Midland, Texas 79701	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FEL & 990' FSL of Sec. 28	8. FARM OR LEASE NAME Cities Federal
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) G.L. 4058'	10. FIELD AND POOL, OR WILDCAT Wildcat
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28, T7S, R37E
	12. COUNTY OR PARISH Roosevelt
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud date & progress

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well, 1-28-75, and drilled a 17½" hole to 500'. Ran 16 jts 13 3/8" 48# H-40 STC 8rd casing and 54.4# J-55 STC casing to 496'. Cemented with 500 sacks Class C with 2% calcium chloride. Displaced plug with 76 BFW. Bumped plug @ 1:30 A.M., 1-31-75 and cement Circulated. WOC 18 hours. Tested casing to 600 psi. Drilled a 12¼" hole to 4056'. Ran 100 jts 8 5/8" 24#, 28#, 32# H-40 J-55 STC casing and set at 4056'. Cemented with 1000 sacks Class C with 2% calcium chloride. Displaced plug with 253 BFW @ 12:25 PM on 2-10-75. WOC 18 hours. Top of cement 1880' via temperature survey. Tested casing to 1000 psi. Drilled at 7 7/8" hole to 9,244'.

18. I hereby certify that the foregoing is true and correct

SIGNED D.C. Radtke (D.C. Radtke) TITLE EngineerDATE 5-19-75

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD

DATE

MAY 21 1975

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side