UNITED STATES SUBMIT IN TRIPLICATE. DEPARTMEN)F THE INTERIOR (Other instructions verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 21513

GEOL	OGICAL	SHRVEY

CHNIDDA	NOTICES	AND	REPORTS	\cap N	WELLS
SUINDICE	ROTHER	MINU	INEL OWID	OI4	YYLLLJ

		6. IF INDIAN, ALLOT	FE OR TRIPE NAME
(Do not use this form !	NOTICES AND REPORTS ON WELLS for proposals to drill or to deepen or plug back to a different reservoir. TAPPLICATION FOR PERMIT—" for such proposals.)		
GAS X	OTHER	7. UNIT AGREEMENT	NAME
2. NAME OF OPERATOR	S. FARM OR LEASE NAME		
H. L. BROWN, JR	Federal "C" 9. WELL NO.		
P.O. Box 2237, 4. Location of Well (Report See also space 17 below.) At surface	1 10. FIELD AND POOL, OR WILLCAT Bluitt(Wolfcamp)Gas		
1650' FWL & 990	' FNL	Sec. 4, T-	EA
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE	
	4064-7 GL	Roosevelt	New Mexico
16. C	heck Appropriate Box To Indicate Nature of Notice, Report, o	r Other Data	-

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:		
			c1	
TEST WATER SHUT-OFF	,	PULL OR ALTER C SING		WATER SHUT-OFF REPAIRING WELL
FRACTI RE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT ALTERING CASING
SHOOT OR ACIDIZE	<u> </u>	ABANDON*		SHOOTING (R ACIDIZING ABANDONMENT*
REPAIR WELL		CHANGE PLANS		(Other) Kull & Set 5-1/2 Casting
(Other)				(NOTE: Report results of multiple completion on Well Comp etion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Drilling at 8095' in Lime and Shale.

Circulated to lay down drill pipe at 8149' total depth in Lime and Dolomite. 7-17:

Deviation 1/2 degree at 8140'. Running logs.

Ran the following 5-1/2' casing;

32 jts. 17# LTC 5-1/2" 1253.60 151 jts. 15.5# LTC 5-1/2" 5700.43' 33 jts. 15.5# STC 5-1/2" 1212.05' 8166.08'

.80' Baker Shoe 2.00' Baker float collar 8168.88' TOTAL

Set at 8149'.

Cemented with 400 sks 50/50 poz, Class C, diamix F, 2% gel, 3/4 of 1% D-31 + 6# salt per sack. Pump plug down 9:05 PM. Released rig at 3 AM. Well shut in waiting on completion unit.

18. I hereby certify that the tookgoing is true and go	· · · · · · · · · · · · · · · · · · ·		
SIGNED Jack R. McGraw		duction Manager	July 21, 1975
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	THE FOR RECORD DATE	X
	*See Instructions on Reverse Side	S. GEOLOGICAL SURVEY	7