

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM -21513

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal "C"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT
Bluitt (Wolfcamp) Gas

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 4, T8S, R37E

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR
H. L. BROWN, JR.

3. ADDRESS OF OPERATOR
P. O. Box 2237, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements *
See also space 17 below.)
At surface

1650' FWL & 990' FNL, Sec. 4, T8S, R37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4064.7 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETION ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) **cementing operations** ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent
to this work.) *

5-30-75: Spudded at 9:30 AM 5-30-75.

5-31-75: Drilled to 510', pulled out of hole to run 12-3/4" surface casing. Picked
up 3 jts. casing and went in hole to 80' and hit bridge. Pulled out of hole with
casing, went in hole with bit. Pushed through bridge 80-100'. Went on to bottom
and circulated. Pulled out of hole and picked up casing, worked through bridge
80-120'. Picked up 18 jts. 12-3/4" 33.30# X-42. Total of 536.67' set at 510'.
Cemented with 300 sks Class C with 2% low dense and 200 sks Class C with 2% CaCl.
Plug down 7:30 AM 5-31-75. Cement circulated.

6-1-75: Waiting on cement.

6-2-75: Draw works on rig being disassembled for repair.

RECEIVED
JUN 3 1975
U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jack K. G. Smith

TITLE

Prod. & Drilg. Manager

DATE

June 3, 1975

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD
JUN 3 1975
U.S. GEOLOGICAL SURVEY
ROBBS, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices either are shown below or may be obtained from the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.