

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

H. L. Brown, Jr.

3. Address and Telephone No.

P O Box 2237, Midland, TX 79702-2237 (915)683-5216

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit L, 1650' FSL, 990' FWL, Sec. 3, T-8S, R-37E

5. Lease Designation and Serial No.

NM-18240A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Federal "F" #1

9. API Well No.

30-041-20406

10. Field and Pool, or Exploratory Area

Bluitt (Wolfcamp)

11. County or Parish, State

Roosevelt County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Currently have: 12-3/4" csg set @ 503', cmt circulated
8-5/8" csg set @ 3648', w/cmt top calculated @ 2350'
5-1/2" csg set @ 8164', w/TOC by Temp Survey @ 6860'
PBSD @ 8118'
Perfs: 8024' - 8085'

Plug as follows: CIBP @ \pm 7975'. Cap w/50 feet of cmt. Free point, cut & retrieve 4-1/2" csg. Pump 150 feet cmt plug @ cut off point. Pump 150 feet cmt plug @ 5000'-5150'. Pump 140 feet cmt plug @ 3600'-3740'. Tag plug. Pump 120 feet cmt plug @ 2190'-2310'. Freepoint, cut, & retrieve 8-5/8" csg. Pump 100 feet cmt plug @ 453'-553'. Tag plug. Pump 60' surface plug. Cut wellhead 3' below surface. Weld on P&A Plate & Marker.

BLM modification.

- * 1. Stub plug needs to be tagged. If cut off point is above 6000' an additional plug will need to be placed in the 4 1/2" casing from 7000'-6860'. Note that if 4 1/2" casing is cut & pulled in area of any of the other required plugs, the stub plug will suffice for that required plug as long as the plug length is at least that of the required plug.
- * 2. Minimum 150' cmt. plug needed across 8 5/8" stub plug. Also note any plug placed in uncemented portion of a casing not pulled would also need same interval plugged in a nucleus.

14. I hereby certify that the foregoing is true and correct

John Gray

Signed

Title Production Engineer

Date 2-10-94

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

Title

Date

approved as modified

FEB 18 1994