

	O. D.	I. D.	LENGTH	DEPTH
Drill Pipe or Tubing				
Reversing Sub				
Water Cushion Valve				
Drill Pipe	4.5"	3.826"	8424'	
Drill Collars	6.25"	2.25"	715'	
Handling Sub & Choke Assembly				
Dual CIP Valve				
Dual CIP Sampler				
Hydro-Spring Tester	5"	.75"	5'	9134'
Multiple CIP Sampler	5"	2.28"	4'	
Extension Joint	5"	-	10' (2)	
AP Running Case				
Hydraulic Jar	5"	1.75"	6'	
VR Safety Joint	5"	1"	3'	
Pressure Equalizing Crossover				
Packer Assembly	6.75"	1.53"	6'	9157'
Distributor				
Packer Assembly	6.75"	1.53"	6'	9163'
Flush Joint Anchor				
Pressure Equalizing Tube				
Blanked-Off B.T. Running Case				
Drill Collars				
Anchor Pipe Safety Joint				
Packer Assembly				
Distributor				
Packer Assembly				
Anchor Pipe Safety Joint				
Side Wall Anchor				
Drill Collars	6.25"	2.25"	29'	
Flush Joint Anchor	5.75"	3.5"	22'	
Blanked-Off B.T. Running Case (2)	5.75"	3.5"	4'	9214' 9218'
Total Depth				9222'