

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-2784-2

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name State 32-7-33 Unit
2. Name of Operator Champlin Petroleum Company	8. Farm or Lease Name
3. Address of Operator 300 Wilco Building Midland, Texas 79701	9. Well No. 15
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>7-S</u> RANGE <u>33-E</u> NMPM.	10. Field and Pool, or Wildcat Chaveroo-San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 4435 GR	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Sitton Drilling Company spudded 3:00 P.M. 11-7-76. Drilled 12½" hole to 1945'. Set 8-5/8" 24# @ 1945' and cemented w/650 sacks lite wated followed by 200 sacks Class "C" w/2% CaCl. Plug down 3:15 A.M. WOC 18 hours. Tested BOP & casing to 800# for 30 minutes, tested OK. Drilled 7-7/8" hole to 4495', set 4½" 10.5# @ 4494' and cemented w/300 sacks Class "H" w/4# salt, ¼# flocele & .3% CFR-2/sack. Plug down 4:30 A.M. 11-15-76. WOC 172 hours. Perforated San Andres 4241, 4243, 4245, 4286, 4288, 4296, 4298, 4300, 4302, 4304, 4306, 4317, 4319, 4321, 4323, 4370, 4372, 4374, 4376, 4378 & 4380' (21 holes). Treated perms w/3750 gals. 15% DS-30 acid. Swabbed tested well. Fractured perms w/51,000 gals. gelled 2% KCL water & 66,500# 20-40 sand. Swabbed tested well. Ran tubing & rods w/BHP for completion.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Walter M. Connelly TITLE District Clerk DATE December 14, 1976

APPROVED BY Jerry S. Smith TITLE Asst. Secy. DATE DEC 14 1976

CONDITIONS OF APPROVAL, IF ANY: