

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐  
2. NAME OF OPERATOR  
SUNDANCE OIL COMPANY  
3. ADDRESS OF OPERATOR  
#510, 1776 Lincoln St., Denver, CO 80203  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
660' FSL, 660' FEL, Unit P  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☒  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
MAR 11 1980  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well has been SI since July, 1979 pending the decision to repair the well (water shut-off) or request permission to convert to a SWD well. At the time of shut-in the well was producing 5 BOPD, 190 BWPD and gas TSTM. At that time the water was being hauled and disposed of at an enormous cost. Also, equipment (rods & tubing) were failing because of the speed and workload required to produce this amount of water (190 BWPD). We request permission to cement squeeze the original perforations in this well (4162' to 4174') and reperforate from 4164' to 4172' and 4145' to 4151' w/2 spf. We anticipate a 20 to 30 BOPD well if the cement squeeze (water shut-off) is successful. This work will be done as soon as approval is received.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Richard O. Dimit*  
Richard O. Dimit

TITLE V-P, Production

DATE March 5, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAR 11 1980

ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side

RECEIVED

MAR 11 1980

~~U.S. DEPARTMENT OF THE INTERIOR~~  
BUREAU OF LAND MANAGEMENT  
WILSON