

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-15019

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
SUNDANCE OIL COMPANY

3. ADDRESS OF OPERATOR
Suite 510, 1776 Lincoln St., Denver, CO 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL and 1980' FWL

Unit C

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4438' KB, 4428' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cone Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Tomahawk San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 31, T. 7S., R. 32E.

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

SET SURFACE CASING ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded 12 1/4" hole at 2:30 p.m. 12/21/77. Drilled to 1800'. Ran 48 jts. of 8 5/8", 24#, surface casing. Set at 1799' KB. Cemented w/400 sx Halliburton Lite w/5#/sx Gilsonite, 1/4#/sx flowseal and 2% CaCl followed by 200 sx Class C and 2% CaCl. Circulated 25 sx cement. Plug down at 11:15 p.m. 12/23/77.

18. I hereby certify that the foregoing is true and correct

SIGNED

Richard O. Dimit

TITLE

Chief Engineer

DATE

December 27, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

ACCEPTED FOR RECORD

JAN 3 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

JAN 10 1960
OIL CONSERVATION COMM.
HOBBS, N. M.

ORDER NOT APPROVED