

COPY TO O. C. C.  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE  
(Other instructions on  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 062178

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Milnesand (San Andres) Unit

8. FARM OR LEASE NAME

9. WELL NO.

521

10. FIELD AND POOL, OR WILDCAT

Milnesand (San Andres)

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 24, T-8-S, R-34-E

12. COUNTY OR PARISH 13. STATE

Roosevelt New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

UNION TEXAS PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

1300 Wilco Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

Unit Letter "H", 2630' FNL & 100' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4239.1' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Casing Test & Cementing

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. October 10, 1978, drilled 7 7/8" hole to a depth of 4615'. WIH with Diamond bbl. @ 4615' & started drilling 7 27/32" hole.
2. October 13, 1978, reached total depth of 4800'. Schlumberger logged total depth of 4803' KB.
3. October 14, 1978, ran 119 jts. (4794') of 5 1/2" K-55 ST&C casing and set @ 4803' KB. Cemented w/1200 sx. Halliburton Lite w/10# salt & 1/4# F.C./sk. Tailed in w/300 sx. of Class "H" cement. Circ. 113 sx. of cement.
4. October 15, 1978, released rig @ 12 A.M. midnight.
5. October 16, 1978, presently waiting on rig to move off.

18. I hereby certify that the foregoing is true and correct

SIGNED Floyd S. Houdyshell

TITLE Production Analyst

DATE 10-17-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 19 1978

GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side