COPY TO O. C. C.

Form 9-331 (May 1963) Form approved. Budget Bureau No. 42-R1424. UNITED JEATES SUBMIT IN TRIPLICATE DEPARTMENT OF THE INTERIOR (Other instructions on re-5. LEASE DESIGNATION AND SERIAL NO. GEOLOGICAL SURVEY LC 062178 6. IF INDIAN, ALLOTTEE OR TRUBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (De not use this form for proposals to deill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.) 7. UNIT AGREEMENT NAME GAS WELL WELL X Milnesand (San Andres) Unit OTHER 8. FARM OR LEASE NAME NAME OF OPERATOR UNION TEXAS PETROLEUM CORPORATION 9. WELL NO. ADDRESS OF OPERATOR LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

At surface 1300 Wilco Building, Midland, Texas 10. FIELD AND POOL, OR WILDCAT Milnesand (San Andres)
11. SEC., T., R., M., GR BLK. AND
SURVEY OR AREA Unit Letter "H", 2630' FNL & 100' FEL Sec. 24, T-8-S, R-34-E 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OR PARISH 13. STATE 14. PERMIT NO. 4239.1' GR Roosevelt New Mexico Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO SUBSEQUENT REPORT OF: PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL TEST WATER SHUT-OFF PRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING SHOOT OR ACHIZE ABANDON* SHOOTING OR ACIDIZING ABANDONMENT⁴ (Other) Casing Test & Cementing CHANGE PLANS REPAIR WELL (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSIDE OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally driled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 1. October 3, 1978, Spudded 12½" hole @ 4:30 A.M. - Drilled to a total depth of 375'. Ran 9 jts. (362') of 8 5/8" 24# X-42 ST&C casing 0 set 0 368'. Cemented w/300 sx. Class "C", 1/4# F.C., 2% CaCl₂. (Circ. 75 sx. cement). Drilled out excess cement & tested casing to 1000# w/no dec. in pressure in 30 minutes. 2. October 4, 1978, presently drilling 7 7/8" hole @ 2100' Anhydrite. ACCEPTED FOR RECORD Prod. Analyst 10-5-78 (This space for Federal or State office use) Ju. S. GEOLOGICAL SUR APPROVED BY CONDITIONS OF APPROVAL, IF ANY: *See Instructions on Reverse Side HOBBS, NEW MEXICO