

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
K-4128

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL" FORM C-101 FOR SUCH PROPOSALS.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Flag-Redfern Oil Company	8. Farm or Lease Name Citgo State
3. Address of Operator P. O. Box 23 Midland, TX 79702	9. Well No. 2
4. Location of Well UNIT LETTER J, 467 FEET FROM THE East LINE AND 2130 FEET FROM THE South LINE, SECTION 16 TOWNSHIP 8-S RANGE 38-E NMPM.	10. Field and Pool, or Willcoat Bluitt (San Andres)
15. Elevation (Show whether DF, RT, GR, etc.) 3982' G.L.	12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

11-23-78 Ran 124 jts 4½" 10.5#/ft J-55, ST&C csg. and set @ 4844'. Cmt w/250 sx 50-50 Class "H" Pozmix, 2% gel, 0.75% CFR-2 8# salt. PD 6:00 AM 11-23-78. WOC 24 hrs. Tested csg to 2000 PSIG for 30 min. held OK.

11-29-78 Picked up tubing and trip in hole to 2311'. Opened stage collar and broke circulation. Cemented with 600 sx Halliburton Light w/0.4% CFR-2 and 8# salt. Circulated 75 sx cement to surface. Closed stage collar and reverse circulated. Pressure casing to 2000#. Held OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Petroleum Engineer DATE 12-12-78
ORIG. SIGNED BY Jerry Sexton
DIST. I, Supv. [Signature] TITLE DATE DEC 18 1978