

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM-17233
2. NAME OF OPERATOR SUNDANCE OIL COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Suite 510, 1776 Lincoln Street, Denver, CO 80203		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FSL and 1980' FEL Unit J		8. FARM OR LEASE NAME Langley Federal
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4415' GL		10. FIELD AND POOL, OR WILDCAT Tomahawk San Andres
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 30, T.7S., R.32E.
		12. COUNTY OR PARISH Roosevelt
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) SET SURFACE CASING ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well at 4:15 p.m. 10/14/78. Drilled 12 1/4" surface hole to 1767'. Ran 44 jts. 23# 8 5/8" surface casing. Set at 1767'. Cemented with 400 sx Halliburton lite mixed with 5# Gilsontite, 1/4# floreal, 2% CaCl followed by 200 sx Class C mixed with 2% CaCl. Circulated 25 sx. Plug down at 5:30 p.m. 10/16/78. WOC 6 hrs. Nippled up BOP's. Tested to 1000#, okay. Drilled out from under surface in 12 hrs.

18. I hereby certify that the foregoing is true and correct

SIGNED

Richard O. Dimit

TITLE Vice President, Production DATE October 18, 1978

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 21 1978

DATE

GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side