16.

SUBMIT IN TRIPLICATES

COPY TO Q.

Budget Bureau No. 42-R1424.

٩K	IMEN	ノト	HE	I NI	EKIUK	
			~		.,	

GEOLOGICAL SURVEY

SUBSEQUENT REPORT OF:

	NM	047	4-B			
6.	IF	INDIAN,	ALLOTTEE	OR	TRIBE	NAME

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	
OIL GAS WELL OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
Petroleum Corporation of Texas	Federal BL
3. ADDRESS OF OPERATOR	9. WELL NO.
P. O. Box 911 Breckenridge, TX 76024	2
L. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.	10. FIELD AND POOL, OR WILDCAT
See also space 17 below.) At surface 990' FNL & 990' FEL,	Bluitt Wolfcamp
NE/4 Section 8, T-8S, R-37E	11. SEC., T., R., M., OR RLK. AND SURVEY OR AREA
	Sec. 8, T-8S, R-37E

12. COUNTY OR PARISH 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. Roosevelt New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

	111211211111111111111111111111111111111				
<u> </u>					
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF REPAIRING WELL			
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT ALTERING CASING			
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING ABANDONMENT®			
REPAIR WELL	CHANGE PLANS	(Other) Cmt surface & intermediate XX			
(Other)		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) *

45'. Spud at 6:30 AM 10/21/78

NOTICE OF INTENTION TO:

638'. Ran 19 jts. 13-3/8" casing. Cemented w/700 sx. Class "C" 2% CC, 10/23/78 Circ. 240 sx. PD at noon.

Set 8-5/8" intermediate string at 3705' in 11" hole w/D.V. Tool at 2118'. 10/28/78 Cement bottom w/300 sx Class "C" & 2% Cal. and 380 sx. Halliburton Lite w/10# salt thru D. V. Tool. Top Cement 500 from suprace Plug down at 6:00 PM.

10/29/78 Nipple up at 4:30 PM, test blind rams @ 1000# for 18 min. Went in hole and tested the hi drill at 1200# for 18 min. Tested pipe rams @ 1200# for 21 min.

Our, Mr. Lowell Moore is sending copies of the test charts today.

10/30 Drilling cement @ 3705'.

8. I hereby certify that the interior is true and correct					· · · · · · · · · · · · · · · · · · ·	·.
SIGNED Arthur Boice		Division	Superintender	it DATE	October	<u>30, 19</u> 7
(This space for Federal or State only the)				on progra	1: 1	
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		NOV Since Side S. GEOL	_^ _	\AMI	- :
*5	iee Instruc	tions on Reve	rse Side S. GEOL	NEW MEXICO	<u>'</u>	