

~~HOBBBS OFFICE 8888~~

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES COPY TO O. G. C.
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1980' FNL & 1980' FEL

AT SURFACE: Unit Letter 'G'

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐
☐

RECEIVED

APR 23 1979

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
HOBBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TOTAL DEPTH 7970'

Plug Back Total Depth 7740'

13 3/8" OD 54.5# K-55 Casing Set @ 384'

8 5/8" OD 32# K-55 Csg Set @ 4500'

5 1/2" OD 17# N-80 Csg Set @ 7950'

1. Perforate 5 1/2" OD Csg w/1-JSPF from 7842' - 7848', 7863' - 7880', & 7892' - 7902'.
2. Set pkr. @ 7775'. Acidize perforations 7842' - 7902' w/2000 gal. 15% NE Acid & 50 ball sealers.
3. Set CIBP @ 7750' w/10' Cement on plug. PBTD 7740'. Perforate 5 1/2" Csg w/1-JSPF from 7609' - 7621'.

(Continued on attached page)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. A. Smith

TITLE Asst. Dist. Supt DATE 4-19-79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

APR 23 1979

U. S. GEOLOGICAL SURVEY
HOBBBS, NEW MEXICO

L. Harris Federal # 2

4. Set Pkr. @ 7565'. Acidize perfs. 7609 - 7621 w/2500 gal. 15% NE Acid & 14 Ball Sealers.
5. Acidize perfs 7609 - 7621 w/10,000 gal 28% NE Acid mixed w/10,000 gal. CO₂. Flushed w/5000 gal fresh water & 5000 gal. CO₂. Job complete 11:50 AM, 3-12-79.
6. Install pumping equipment & construct electrical lines.
7. On 24 Hrs. potential test ending 1:00 PM, 4-17-79, well pumped 41 B0, 96 BW, GOR TSTM.

RECEIVED

APR 24 1979

OIL COMPANY

APR 24 1979